

### CLAIMS

1. (Currently Amended) A lid for a utility box comprising:

a compression molded solid member ~~compression molded from~~ of plastic material and having spaced apart upper and lower sides and an outer edge,

said outer edge extends around said member next to said lower side and which faces outward of said member,

said lower side comprising a lower surface which is contiguous with said outer edge at least on two opposite sides of said outer edge,

a plurality of spaced apart recesses having outer edges at said lower surface which are spaced from said outer edge of said member such that said lower surface surrounds said outer edges of said recesses,

said recesses being formed during the molding process to enhance curing of the plastic material and hence the quality of the lid,

each of said recesses comprises a surface which extends from its said outer edges into said member,

the area of said lower surface being greater than the total area surrounded by said outer edges of said recesses,

said member of said lid has the strength sufficient to withstand a load of at least 8,000 pounds applied to the upper side when the lower side is supported by means placed around a perimeter of said member.

2. (Original) The lid of claim 1, wherein:
  - said lower surface is a generally planar surface,
  - said upper side is a generally planar upper surface,
  - a plurality of spaced apart wedges formed on said outer edge of said member which extend outward of said outer edge at said upper surface and taper toward said lower surface.
3. (Previously Amended) The lid of claim 1, wherein:
  - said outer edges of each of said recesses comprise two spaced apart elongated outer edges and two spaced apart shorter outer edges,
  - said elongated edges of said recesses are generally parallel with each other,
  - said member has a given dimension along which said elongated edges of said recesses extend,
  - the lengths of said elongated edges of said recesses are greater than one half of said given dimension of said member.
4. (Previously Amended) The lid of claim 3, wherein:
  - said outer edge of said member is rectangular in shape and comprises a first pair of spaced apart edges and a second pair of spaced apart edges with said first pair of edges being transverse to said second pair of edges,
  - said elongated edges of said recesses are generally parallel with said first pair of edges of said member.

5. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~ of plastic material and having spaced apart upper and lower sides and an outer edge,

said outer edge extends around said member next to said lower side and which faces outward of said member,

said lower side comprising a lower surface which is contiguous with said outer edge at least on two opposite sides of said outer edge,

a plurality of spaced apart recesses having outer edges at said lower surface which are spaced from said outer edge of said member such that said lower surface surrounds said outer edges of said recesses,

said recesses being formed during the molding process to enhance curing of the plastic material and hence the quality of the lid,

each of said recesses comprises a surface which extends from its said outer edges into said member,

said outer edges of each of said recesses comprise two spaced apart elongated outer edges and two spaced apart shorter outer edges,

said elongated edges of said recesses are generally parallel with each other,

said member has a given dimension along which said elongated edges of said recesses extend,

the lengths of said elongated edges of said recesses are greater than one half of said given dimension of said member,

said member of said lid has the strength sufficient to withstand a load of at least 8,000 pounds applied to said upper side when said lower side is supported by means placed around a the perimeter of said member.

6. (Previously Amended) The lid of claim 5, wherein:

said outer edge of said member is rectangular in shape and comprises a first pair of spaced apart edges and a second pair of spaced apart edges with said first pair of edges being transverse to said second pair of edges,

said elongated edges of said recesses are generally parallel with said first pair of edges of said member.

7. (Original) The lid of claim 5, wherein:

said lower surface is a generally planar surface,

said upper side is a generally planar upper surface,

a plurality of spaced apart wedges formed on said outer edge of said member which extend outward of said outer edge at said upper surface and taper toward said lower surface.

8. (Cancelled)

9. (Previously Added) The lid of claim 1, wherein:

said lower surface is generally a planar surface.

10-11 (Cancelled)

12. (Previously Added) The lid of claim 5, wherein:

the area of said lower surface is greater than the total area surrounded by said outer edges of said recesses.

13. (Previously Added) The lid of claim 5, wherein:

said lower surface is a generally planar surface.

14. (Cancelled)

15. (Previously Added) The lid of claim 1, wherein:

one of said plurality of recesses comprises two spaced apart elongated edges and two spaced apart shorter outer edges,

a second of said plurality of recesses has dimensions in two directions transverse to each other each of which is greater than the dimensions of said shorter outer edges of said one recess.

16. (Previously Amended) The lid of claim 1, wherein:

said plurality of recesses comprises at least three recesses,

said outer edges of each of two of said plurality of recesses comprise two spaced apart elongated outer edges and two spaced apart shorter outer edges,

one of said plurality of recesses has dimensions in two directions transverse to each other which are greater than the dimensions of said shorter outer edges of either of said two recesses.

17. (Previously Amended) The lid of claim 15, wherein:

said member of said lid is a solid member molded solely from a plastic material,

said upper side comprises an upper surface,

an upper recess formed in said upper surface of said lid at least partially in alignment with said second recess.

18. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~ of plastic material and having spaced apart upper and lower sides and an outer edge,

said outer edge comprising a first pair of spaced apart outer edges which face in opposite directions from each other outward from said member and a second pair of spaced apart outer edges which face in opposite direction from each other outward from said member,

said first pair of outer edges being transverse to said second pair of opposite edges,

said lower side comprising a lower surface which extends to and is contiguous with said first and second pairs of outer edges,

a plurality of spaced apart recesses formed in said lower surface and spaced from said outer edge of said lower surface and from said upper side,

said recesses being formed during the molding process to enhance curing of the plastic material and hence the quality of the lid,

one of said recesses comprising two spaced apart elongated edges and two spaced apart shorter edges,

said lower surface having a given dimension along which said elongated edges extend,

the lengths of said elongated edges of said one recess are greater than one half of said given dimension of said surface,

said member of said lid has the strength sufficient to withstand a load of at least 8,000 pounds applied to said upper side when said lower side is supported by means placed around a the perimeter of said member.

19. (Previously Added) The lid of claim 18, wherein:

a second of said plurality of recesses has dimensions in two directions transverse to each other each of which is greater than the dimensions of said shorter edges of said one recess.

20. (Previously Added) The lid of claim 18, wherein:

said one recess comprises two generally flat surfaces extending along said two elongated edges respectively and which join each other along a line such that said two surfaces and a plane extending across

said recess at said lower surface defines a triangle as seen in cross-sections transverse to said elongated edges with said line located between said upper and lower surfaces.

21. (Previously Added) The lid of claim 20, wherein:

a second of said plurality of recesses has dimensions in two directions transverse to each other each of which is greater than the dimensions of said shorter edges of said one recess.

22. (Previously Added) The lid of claim 21, wherein:

said line has opposite ends,

said one recess comprises two triangular shaped surfaces extending from said shorter edges to said opposite ends of said line respectively such that, said two triangular shaped surfaces extend away from each other from said opposite ends of said line to said shorter edges respectively.

23. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded solely from~~ of a single type of plastic material and having spaced apart upper and lower sides and an outer edge,

said outer edge comprising a first pair of spaced apart outer edges which face in opposite directions from each other outward from said member and a second pair of spaced apart outer edges which face in opposite direction from each other outward from said member,



said first pair of outer edges being transverse to said second pair of opposite edges,

said lower side comprising a lower surface which extends to and is contiguous with said first and second pairs of outer edges,

first and second spaced apart recesses, generally parallel to each other, formed in said lower surface and spaced from said outer edge of said lower surface and from said upper side,

said recesses being formed during the molding process to enhance curing of the plastic material and hence the quality of the lid,

each of said first and second recesses comprising two spaced apart elongated edges and two spaced apart shorter edges with two generally flat surfaces extending along said two elongated edges respectively and which join each other along a line such that said two surfaces and a plane extending across said recess at said lower surface define a triangle as seen in cross-sections transverse to said elongated edges with said line located between said upper and lower surfaces,

the dimensions of said lower surface between said first and second spaced apart recesses being greater than the dimensions of said shorter edges of either of said first and second recesses,

said member of said lid has the strength sufficient to withstand a load of at least 8,000 pounds applied to the upper side when the lower side is supported by means placed around a perimeter of said member.

24. (Currently Amended) The lid of claim 23, comprising:

a third recess formed in said lower surface spaced from said first and second recesses and from said outer edge of said lower surface and having dimensions in two directions transverse to each other each of which is greater than the dimensions of said shorter edges of either of said first and second recesses.

25. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded solely from~~ of a single type of plastic material and having spaced apart upper and lower sides and an outer edge,

said outer edge comprising a first pair of spaced apart outer edges which face in opposite directions from each other outward from said member and a second pair of spaced apart outer edges which face in opposite direction from each other outward from said member,

said first pair of outer edges being transverse to said second pair of opposite edges,

said lower side comprising a lower surface which extends to and is contiguous with said first and second pairs of outer edges,

a plurality of spaced apart recesses formed in said lower surface and spaced from said outer edge of said lower surface and from said upper side,

said recesses being formed during the molding process to enhance curing of the plastic material and hence the quality of the lid,

one of said recesses comprising two spaced apart elongated edges and two spaced apart shorter edges,

a second of said plurality of recesses has dimensions in two directions transverse to each other each of which is greater than the dimensions of said shorter edges of said one recess,

said member of said lid has the strength sufficient to withstand a load of at least 8,000 pounds applied to said upper side when said lower side is supported by means placed around a the perimeter of said member.

26. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded solely from of~~ a single type of plastic material and having spaced apart upper and lower sides and an outer edge,

said outer edge extends around said member next to said lower side and which faces outward of said member,

said lower side comprising a lower surface which is contiguous with said outer edge at least on two opposite sides of said outer edge,

at least one recess formed in said lower surface and spaced from said outer edge of said lower surface and from said upper side,

said one recess being formed during the molding process to enhance curing of the plastic material and hence the quality of the lid,

said one recess comprising two spaced apart elongated edges and two spaced apart shorter edges with two generally flat surfaces extending along said two elongated edges respectively and which join

each other along a line such that said two surfaces and a plane extending across said recess at said lower surface define a triangle as seen in cross-sections transverse to said elongated edges with said line located between said upper and lower surfaces,

said lower side having a given dimension along which said elongated edges of said recess extend,

the lengths of each of said elongated edges are equal to a substantial portion of the length of said given dimension,

said member of said lid has the strength sufficient to withstand a load of at least 8,000 pounds applied to the upper side when the lower side is supported by means placed around a perimeter of said member.

27. (Previously Added) The lid of claim 26, wherein:

said line has opposite ends,

said recess comprises two triangular shaped surfaces extending from said shorter edges to said opposite ends of said line respectively such that said two triangular shaped surfaces extend away from each other from said opposite ends of said line to said shorter edges respectively.

28. (Previously Added) The lid of claim 26, wherein:

the lengths of each of said elongated edges of said recess are greater than one half of said given dimensions.

29. (Previously Added) The lid of claim 27, wherein:  
the lengths of each of said elongated edges of said recess are greater than one half of said given dimensions.
30. (Previously Added) The lid of claim 26, comprising:  
a second recess formed in said lower surface and spaced from said outer edge of said lower surface and from said upper side,  
said second recess has dimensions in two directions transverse to each other which are greater than the dimensions of said shorter edges of said one recess.
31. (Currently Amended) A lid for a utility box, comprising:  
a compression molded solid member ~~compression molded~~  
~~solely from of~~ a single type of plastic material and having spaced apart upper and lower sides and an outer edge,  
said outer edge comprising a first pair of spaced apart outer edges which face in opposite directions from each other outward from said member and a second pair of spaced apart outer edges which face in opposite direction from each other outward from said member,  
said first pair of outer edges being transverse to said second pair of opposite edges,  
said lower side comprising a lower surface which extends to and is contiguous with said first and second pairs of outer edges,

first and second spaced apart recesses, generally parallel to each other, formed in said lower surface and spaced from said outer edge of said lower surface and from said upper side,

said recesses being formed during the molding process to enhance curing of the material and hence the quality of the lid,

each of said first and second recesses comprising two spaced apart elongated edges and two spaced apart shorter edges with two generally flat surfaces extending along said two elongated edges respectively and which join each other along a line such that said two surfaces and a plane extending across said recess at said lower surface define a triangle as seen in cross-sections transverse to said elongated edges with said line located between said upper and lower surfaces,

said member of said lid has the strength sufficient to withstand a load of at least 8,000 pounds applied to the upper side when the lower side is supported by means placed around a perimeter of said member.

32. (Previously Added) The lid of claim 31, wherein:

each of said lines has opposite ends,

each of said recesses comprises two triangular shaped surfaces extending from its said shorter edges to said opposite ends of its said line respectively such that said two triangular shaped surfaces extend away from each other from said opposite ends of said line to said shorter edges respectively.

33. (Previously Added) The lid of claim 31, wherein:  
the lengths of each of said elongated edges of said recess are  
greater than one half of said given dimension.
34. (Previously Added) The lid of claim 32, wherein:  
the lengths of each of said elongated edges of said recess are  
greater than one half of said given dimension.
35. (Previously Added) The lid of claim 31, comprising:  
a second recess formed in said lower surface and spaced from  
said outer edge of said lower surface and from said upper side,  
said second recess has dimensions in two directions transverse  
to each other which are greater than the dimensions of said shorter  
edges of said recesses.
36. (Cancelled)
37. (Previously Amended) The lid of claim 1, wherein:  
said member of said lid is molded solely from a single type of  
plastic material.
38. (Previously Amended) The lid of claim 36, wherein:  
said member of said lid is molded solely from a single type of  
plastic material.

39. (Previously Amended) The lid of claim 5, wherein:  
said member of said lid is molded solely from a single type of plastic material.
40. (Previously Amended) The lid of claim 18, wherein:  
said member of said lid is molded solely from a single type of plastic material.
41. (Cancelled)
42. (Currently Amended) The lid of claim 23, wherein:  
said plastic material has a density range of .938-.942 .
43. (Previously Amended) The lid of claim 41, wherein:  
said member of said lid is molded solely from a single type of plastic material.
44. (Previously Amended) The lid of claim 25, wherein:  
said plastic material has a density range of .938-.942.
- 45-46 (Cancelled)
47. (Previously Amended) The lid of claim 45, wherein:  
said member of said lid is molded solely from a single type of plastic material.



48-57 (Cancelled)

58. (Currently Amended) A lid for a utility box comprising:

~~a compression molded solid member compression molded from~~  
~~of a plastic material as a single layer of material and~~ having spaced  
apart upper and lower sides and an outer edge,

said lower side comprising a lower surface,

a plurality of spaced apart recesses having outer edges at said  
lower surface which are spaced from said outer edge of said member  
such that said lower surface surrounds said outer edges of said  
recesses,

said recesses being formed during the molding process to  
enhance curing of the plastic material and hence the quality of the lid,

each of said recesses comprises a surface which extends from  
its said outer edges into said member,

the area of said lower surface being greater than the total area  
surrounded by said outer edges of said recesses,

said member of said lid has the strength sufficient to withstand  
a load of at least 8,000 pounds applied to the upper side when the  
lower side is supported by means placed around a perimeter of said  
member.

59. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~  
of a plastic material as a single layer of material and having spaced  
apart upper and lower sides and an outer edge,

said lower side comprising a lower surface,

a plurality of spaced apart recesses having outer edges at said  
lower surface which are spaced from said outer edge of said member  
such that said lower surface surrounds said outer edges of said  
recesses,

said recesses being formed during the molding process to  
enhance curing of the plastic material and hence the quality of the lid,

each of said recesses comprises a surface which extends from  
its said outer edges into said member,

said outer edges of each of said recesses comprise two spaced  
apart elongated outer edges and two spaced apart shorter outer edges,

said elongated edges of said recesses are generally parallel with  
each other,

said member has a given dimension along which said elongated  
edges of said recesses extend,

the lengths of said elongated edges of said recesses are greater  
than one half of said given dimension of said member,

said member of said lid has the strength sufficient to withstand  
a load of at least 8,000 pounds applied to said upper side when said  
lower side is supported by means placed around a ~~the~~ perimeter of  
said member.

60. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~  
~~of a plastic material as a single layer of material~~ and having spaced  
apart upper and lower sides,

said lower side comprising a lower surface having an outer  
edge,

a plurality of spaced apart recesses formed in said lower surface  
and spaced from said outer edge of said lower surface and from said  
upper side,

said recesses being formed during the molding process to  
enhance curing of the plastic material and hence the quality of the lid,

one of said recesses comprising two spaced apart elongated  
edges and two spaced apart shorter edges,

said lower surface having a given dimension along which said  
elongated edges extend,

the lengths of said elongated edges of said one recess are  
greater than one half of said given dimension of said surface,

said member of said lid has the strength sufficient to withstand  
a load of at least 8,000 pounds applied to said upper side when said  
lower side is supported by means placed around a the perimeter of  
said member.

61. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~  
of a plastic material as a single layer of material and having spaced  
apart upper and lower sides,

said lower side comprising a lower surface having an outer  
edge,

first and second spaced apart recesses, generally parallel to each  
other, formed in said lower surface and spaced from said outer edge of  
said lower surface and from said upper side,

said recesses being formed during the molding process to  
enhance curing of the plastic material and hence the quality of the lid,

each of said first and second recesses comprising two spaced  
apart elongated edges and two spaced apart shorter edges with two  
generally flat surfaces extending along said two elongated edges  
respectively and which join each other along a line such that said two  
surfaces and a plane extending across said recess at said lower surface  
define a triangle as seen in cross-sections transverse to said elongated  
edges with said line located between said upper and lower surfaces,

the dimensions of said lower surface between said first and  
second spaced apart recesses being greater than the dimensions of said  
shorter edges of either of said first and second recesses,

said member of said lid has the strength sufficient to withstand  
a load of at least 8,000 pounds applied to the upper side when the  
lower side is supported by means placed around a perimeter of said  
member.

62. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~  
~~of a plastic material as a single layer of material~~ and having spaced  
apart upper and lower sides,

said lower side comprising a lower surface having an outer  
edge,

a plurality of spaced apart recesses formed in said lower surface  
and spaced from said outer edge of said lower surface and from said  
upper side,

said recesses being formed during the molding process to  
enhance curing of the plastic material and hence the quality of the lid,

one of said recesses comprising two spaced apart elongated  
edges and two spaced apart shorter edges,

a second of said plurality of recesses has dimensions in two  
directions transverse to each other each of which is greater than the  
dimensions of said shorter edges of said one recess,

said member of said lid has the strength sufficient to withstand  
a load of at least 8,000 pounds applied to said upper side when said  
lower side is supported by means placed around a the perimeter of  
said member.

63. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~  
~~of a plastic material as a single layer of material~~ and having spaced  
apart upper and lower sides,

said lower side comprising a lower surface having an outer  
edge,

at least one recess formed in said lower surface and spaced  
from said outer edge of said lower surface and from said upper side,

said one recess being formed during the molding process to  
enhance curing of the plastic material and hence the quality of the lid,

said one recess comprising two spaced apart elongated edges  
and two spaced apart shorter edges with two generally flat surfaces  
extending along said two elongated edges respectively and which join  
each other along a line such that said two surfaces and a plane  
extending across said recess at said lower surface define a triangle as  
seen in cross-sections transverse to said elongated edges with said line  
located between said upper and lower surfaces,

said member of said lid has the strength sufficient to withstand  
a load of at least 8,000 pounds applied to the upper side when the  
lower side is supported by means placed around a perimeter of said  
member.

64. (Previously Added) The lid of claim 63, wherein:

said lower side has a dimension along which said elongated  
edges extend,

the lengths of each of said elongated edges are equal to a substantial portion of the lengths of said given dimension.

65. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~  
~~of a plastic material as a single layer of material~~ and having spaced  
apart upper and lower sides,

said lower side comprising a lower surface having an outer  
edge,

first and second spaced apart recesses, generally parallel to each  
other, formed in said lower surface and spaced from said outer edge of  
said lower surface and from said upper side,

said recesses being formed during the molding process to  
enhance curing of the material and hence the quality of the lid,

each of said first and second recesses comprising two spaced  
apart elongated edges and two spaced apart shorter edges with two  
generally flat surfaces extending along said two elongated edges  
respectively and which join each other along a line such that said two  
surfaces and a plane extending across said recess at said lower surface  
define a triangle as seen in cross-sections transverse to said elongated  
edges with said line located between said upper and lower surfaces,

said member of said lid has the strength sufficient to withstand  
a load of at least 8,000 pounds applied to the upper side when the  
lower side is supported by means placed around a perimeter of said  
member.

66. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~  
of plastic material having upper and lower sides and an outer edge;

a plurality of spaced apart recesses located in the lower side, the  
recesses having a depth which is the distance the recesses extend  
toward the other side;

the member having a thickness between the upper and lower  
side;

the depth of the recesses being no greater than two-thirds of the  
member thickness;

the member of the lid having the strength sufficient to  
withstand a load of at least 8000 pounds applied to the upper side  
when the lower side is supported by means placed around a the  
perimeter of the member.

67. (Previously Added) The lid of claim 66 wherein the member thickness  
is at least one and one-half inches.

68. (Previously Added) The lid of claim 66 wherein the recesses are first  
recesses, the lid further comprising at least one remote reading  
equipment recess located in the lower side.

69. (Currently Amended) A lid for a utility box, comprising:



a compression molded solid member ~~compression molded from~~  
of plastic material having upper and lower sides and an outer edge;

the lower side comprising a lower surface that is contiguous  
with portions of the outer edge;

a plurality of spaced apart recesses located in the lower side, the  
recesses having a depth which is the distance the recesses extend  
toward the upper side;

at least some of the recesses being spaced apart from each other  
a distance that is greater than the depth of the respective recesses;

the member of the lid having the strength sufficient to  
withstand a load of at least 8000 pounds applied to the upper side  
when the lower side is supported by a means placed around a  
perimeter of the member.

70. (Previously Added) The lid of claim 69 wherein the member thickness  
is at least one and one-half inches.

71. (Currently Amended) A lid for a utility box, comprising:

a compression molded solid member ~~compression molded from~~  
of plastic material having upper and lower sides and an outer edge;

the lower side comprising a lower surface that is contiguous  
with portions of the outer edge;

a plurality of spaced apart recesses located in the lower side, the  
recesses having a depth which is the distance the recesses extend  
toward the upper side;

the member having a thickness between the upper and lower sides of at least one and a half inches;

the member of the lid having the strength sufficient to withstand a load of at least 8000 pounds applied to the upper side when the lower side is supported by means placed around a the perimeter of the member.

72. (New) A lid for a utility box, comprising:

a compression molded solid member of plastic material having spaced apart upper and lower sides,

the lower side comprising a lower surface having an outer edge, at least one recess formed in the lower surface and spaced from the outer edge of the lower surface and from the upper side,

the one recess formed during the molded process to enhance curing of the plastic material and hence the quality of the lid,

said member of said lid has the strength sufficient to withstand a load of at least 8,000 pounds applied to the upper side when the lower side is supported by means placed around a perimeter of said member.

73. (New) The lid of claim 72 wherein the member thickness is at least one and one half inches.

74. (New) The lid of claim 72 wherein the recess is a remote reading equipment recess.

75. (New) The lid of claim 72 wherein the member of the lid has the strength sufficient to withstand a load of at least 9,000 pounds applied to the upper side when the lower side is supported by means placed around the perimeter of the member.